


Schlauchverbindungsteile mit hoher Festigkeit, Zähigkeit, geringem Gewicht, Abriebfestigkeit und großer Schlagfestigkeit.

Temperaturbereich -40 °C bis 80 °C  
 Arbeitsdruck max. 10 bar



34.413

## Gerader Schlauchverbindungsstutzen, POM

| Artikel Nr. | Typen Nr. | für Schlauch         |  | Innen-Ø<br>D <sub>2</sub><br>mm | L <sub>1</sub><br>mm |
|-------------|-----------|----------------------|--|---------------------------------|----------------------|
|             |           | D <sub>1</sub><br>mm |  |                                 |                      |
| 110988      | 34.410    | LW 3                 |  | 2,5                             | 25,0                 |
| 110989      | 34.411    | LW 4                 |  | 2,7                             | 35,0                 |
| 110990      | 34.411/5  | LW 5                 |  | 3,0                             | 45,0                 |
| 110991      | 34.412    | LW 6                 |  | 4,0                             | 49,0                 |
| 110992      | 34.413    | LW 8                 |  | 5,6                             | 56,0                 |
| 110993      | 34.414    | LW 10                |  | 7,0                             | 63,0                 |
| 110994      | 34.415    | LW 12                |  | 8,6                             | 66,5                 |
| 110995      | 34.416    | LW 13                |  | 8,6                             | 73,0                 |
| 110996      | 34.417    | LW 16                |  | 12,0                            | 75,0                 |
| 110997      | 34.418    | LW 19                |  | 15,0                            | 76,0                 |
| 110998      | 34.419    | LW 25                |  | 21,0                            | 95,0                 |